















Relay Type	SR2M	SR4 D/M	SR6 D/M	SR6 (V23050)	SR6Z
					
					
RoHS Status	Compliant	Compliant	Compliant	Compliant	Compliant
<b>Contacts</b>					
Configuration	1 N/O + 1 N/C, 2 C/O	2 N/O + 2 N/C 3 N/O + 1 N/C	2 N/O + 2 N/C 3 N/O + 1 N/C	4 N/O + 2 N/C, 3 N/O + 3 N/C, 5 N/O + 1 N/C	4 N/O + 2 N/C, 3 N/O + 3 N/C 5 N/O + 1 N/C
Rated current	6 A	8 A	8 A	8 A	8 A
Rated voltage (VAC)	240/400 VAC	240/400 VAC	240/400 VAC	240/400 VAC	240/240 VAC
Maximum breaking capacity AC	1500 VA	2000 VA	2000 VA	2000 VA	2000 VA
Contact material	AgNi	AgSnO <sub>2</sub>	AgSnO <sub>2</sub>	AgSnO <sub>2</sub>	AgSnO <sub>2</sub>
<b>Coil</b>					
Coil voltage range (DC/AC)	5 - 110 V / -	5 - 110 V / -	5 - 110 V / -	5 - 110 V / -	6 - 115 V / 12 - 230 V
Coil power	700mW / -	800mW / -	1.2W / -	1.2W / -	1.2 W
Other coil versions				800 mW sensitive coil	
<b>General data</b>					
Dielectric strength coil - contacts	4000 VAC	4000 VAC	3000 VAC	4000 VAC	3000 VAC
Clearance /creepage coil - contacts	8 / 8 mm	10 / 10 mm	5.5 / 5.5 mm	5.5 / 5.5 mm	5.5 / 5.5 mm
Temperature range / °C	- 25 to + 70	-25 to +70	-25 to +70	- 25 to + 70	-25 to +50
Sealing	Washable	Washable	Washable	Washable	-
Termination method	PCB	PCB	PCB	PCB	Spring Clamp
Dimensions (l x w x h) / mm	29 x 12.6 x 25.5	40 x 13 x 16.5	55 x 16.5 x 16.5	55 x 16.5 x 16.5	87 x 46 x 54
Approvals (Technical data on approved types on request)	VDE, cULus, TUV	VDE, cULus, TUV	VDE, cULus, TUV	VDE, cULus, TUV	CE

## CIRCUIT BREAKERS

Relay Type	W28	W54	W57	W51	W6/9
					
<b>Type</b>	Thermal	Thermal	Thermal	Thermal	magnetic
<b>Electrical Data</b>					
Number of poles	1	1	1	1	1 through 4
Current rating	0.25 - 16 A	5 - 40 A	4 - 20 A	5 - 20 A	0.25 - 50 A
Max. operating voltage	32 VDC, 250 VAC	50 VDC, 250 VAC	50 VDC, 250 VAC	50 VDC, 250 VAC	277 VAC
Interrupt capacity	1000 A at 32 VDC or 250 VAC	1000 Amps	1000 Amps	1000 Amps	2000 A at 65 VDC, 5000 A at 277 VAC
<b>General data</b>					
Temperature range (°C)	-20 to +60	0 to +60	0 to +60	0 to +60	-40 to +85
Termination method	6.35mm Quick connect	Quick connect or screw	Quick connect	Quick connect or PCB	Quick connect, studs
Dimensions mm (L x W x H)	13.7 x 15.9 x 40	35 x 14.9 x 59	29.2 x 14.6 x 46	33.3 x 12.8 x 36.3	19.1 x 63.5 x 53.0
Approvals (Technical data on approved types on request)	VDE, UL, CSA, DEMKO, SEV	cULus	cULus	cULus	VDE, UL, CSA