

















Relay Type	XT	PT	PTF	MT
				
				
RoHS Status	Compliant	Compliant	Compliant	Compliant
Contacts				
Configuration	1 or 2 C/O	2 / 3 / 4 C/O	2 C/O	2 / 3 C/O
Rated current	16 / 8 A	12 / 10 / 6 A	15 / 10A	10 A
Rated voltage (VAC)	240/400 VAC	240/400 VAC	240/400 VAC	240/400 VAC
Maximum breaking capacity AC	4000 VA or 2000 VA	3000 / 2500 / 1500 VA	1800 / 2500 VA	2500 VA
Contact material	AgNi90/10	AgNi90/10	AgNi90/10	AgNi90/10
Coil				
Coil voltage range (DC/AC)	6 - 110 / 24 - 230	6 - 220 / 6 - 230	6 - 220 / 6 - 230	6 - 220 / 6 - 230
Coil power	400 mW / 0.75 VA	0.75 mW / 1.0 VA	750 mW / 1.0 VA	1.2 W / 2.3 VA
General data				
Dielectric strength coil - contacts	up to 5000 VAC	2500 VAC	2500 VAC	2500 VAC
Clearance /creepage coil - contacts	8 / 8 mm	4 / 4 mm	3.1 / 3.1 mm	2.8 / 4 mm
Temperature range / °C	- 40 to + 70	- 40 to + 70	- 40 to +70	- 40 to + 50/60
Sealing	Flux tight	Flux tight	Flux tight	Dustproof
Termination method	Plug-in	Plug-in, PCB	Plug-in, PCB	Plug-in
Dimensions (l x w x h) / mm	29 x 13.7 x 26.7	28 x 22.5 x 29	28 x 22.5 x 29	35.5 x 35.5 x 57
Approvals (Technical data on approved types on request)	VDE, cULus	VDE, cULus, LLOYD'S	VDE, cULus	VDE, cULus

Relay Type	RM 2/3/7	RM 5/6	RM 8	RMC/ RMD
				
				
RoHS Status	Compliant	Compliant	Compliant	Compliant
Contacts				
Configuration	2 C/O, 3 C/O	2 or 3 N/O 3mm gap	2 C/O	1 N/O + 1 N/C, 1 N/O
Rated current	16 / 10 A	16 / 10 A	25 A	30 A
Rated voltage (VAC)	400 / 440 VAC	230 / 440 VAC	400 VAC	400 / 440 VAC
Maximum breaking capacity AC	6000 / 3800 VA	6000 / 3800 VA	6000 VA	7500 VA
Contact material	AgNi90/10, AgCdO	AgNi90/10, AgCdO	AgNi90/10, AgCdO	AgNi90/10, AgCdO
Coil				
Coil voltage range (DC/AC)	6 - 220 / 6 - 400	6 - 220 / 6 - 400	6 - 220 / 6 - 400	6 - 220 / 6 - 400
Coil power	1.2 - 1.6 W / 2.3 - 2.8 VA	1.6 W / 2.8 VA	1.2W / 2.8 VA	1.2W / 2.8 VA
General data				
Dielectric strength coil - contacts	2500 VAC	2500 VAC	2500 VAC	2500 VAC
Clearance /creepage coil - contacts	4 / 14.9 mm	4 / 14.9 mm	4 / 14.9 mm	4 / 14.9 mm
Temperature range / °C	- 45 to + 50 / 70	- 45 to + 50 / 60	- 45 to + 40 / 65	- 45 to + 40 / 60
Sealing	Dust proof	Dust proof	Dust proof	Dust proof
Termination method	Plug-in, DIN rail, PCB	Plug-in, DIN rail, PCB	Plug-in, DIN rail	Flange + Quick connect
Dimensions (l x w x h) / mm	38.5 x 35.5 x 48.5	38.5 x 35.5 x 48.5	38.5 x 35.5 x 48.5	38.5 x 35.5 x 48.5
Approvals (Technical data on approved types on request)	VDE, cULus	VDE, cULus	VDE, cULus	cULus